



Philips
Magic 5 Eco Primo
Plain paper fax with
telephone and copier

Magic 5 Eco Primo



PPF 631E

Fax it, say it

All Magic 5 Eco faxes have a high energy efficiency. Furthermore these feature rich fax devices are perfectly adapted to your needs and the stylish design heightens the pleasure of communicating.

Plain paper fax

- Stores up to 15 pages
- Provides predefined fax forms

Feature rich telephone

- Features distinctive ring tones
- Allows redial of last 10 numbers

Easy to use copier

- Multicopies up to 15 pages
- Prints in fine-/photo resolution

High energy efficiency

- Philips is 43% better on energy efficiency compared to the average of the competitors



asimpleswitch.com

PHILIPS

Product Specifications

Main features

Ink-film fax

- ITU Group 3 compatible (T.30 standard/T.30 new)
- 9.600 bps modem speed, auto fall back
- Horizontal resolution: 8 pixels/mm
vertical resolution standard: 3.85 lines/mm
vertical resolution fine: 7.7 lines/mm
- Page header, automatic redial
- Sending report with reduced copy of the first page
- Printing method: thermal transfer
- 10 page automatic document feeder (ADF)
- Predefined fax forms
- Sudoku printing with solutions (easy - medium - tough - devil)
- Timer function (send later)
- Up to 15 page memory
- Group broadcasting
- Easy polling (receive and send)
- Paper tray up to 50 sheets
- Cordless phone management

Telephone

- 50 name dial entries
- 10 ringer melodies
- Caller identification (CLIP)*
- Distinctive ring tones**
- 10 short dial keys
- On hook dialling
- Chain dialling
- Redial of the last 10 numbers
- Outgoing call log print

Copier

- Multicopy up to 15 pages
- Fine-/photo-resolution
- Zoom-function (enlarge/reduce)
- 16 grey scales

* Depends on the availability of the service on the local operators network

** Depends on the availability of caller identification

General Information

Power consumption

- Stand by typ. 1,4 W
- Transmission typ. 15 W
- Reception typ. 15 W
- Copy typ. 15 W
- Telephone conversation typ. 4 W

Display

- Liquid crystal-display (LCD), 16 characters/
1 line, European characters

Installation

- Easy-install menu and help pages

Dimensions (WxDxH)

- Unpacked 313x197x129mm
- Packed 377x247x200mm

Weight

- Unpacked (without accessories) 2,3 kg
- Packed (incl. country kit) 3 kg

Temperature range

- Operation 5° C - 40° C
- Storage packed -25° C - 50° C
- Storage unpacked 0° C - 45° C

Relative humidity

- Operation 15 - 85 %
- Storage packed 5 - 95 %
- Storage unpacked 15 - 85 %

Standard package includes

- Fax machine incl. cables (mains and telephone network)
- Starter ink film
- User-manual including installation-guide

Accessories

- Philips PFA 351 with PLUG'N'PRINT Card/
up to 140 pages A4
- Philips PFA 352 with PLUG'N'PRINT Card/
up to 90 pages A4

9 NC	28813XXXXX
Type number	PPF 63 IE/XXB
EAN code	3425160XXXXXX
Designed for	PSTN/PABX
Power supply	195 - 264V AC/ 47 - 63Hz



PHILIPS and the PHILIPS' Shield Emblem are registered trademarks of Koninklijke Philips Electronics N.V. and are used by Sagem Communications under license from Koninklijke Philips Electronics N.V.

www.fax.philips.com

© 2008 Sagem Communications Austria GmbH.
All rights reserved. The information and specifications included are subject to change without prior notice. Sagem Communications tries to ensure that all information in this document is correct, but does not accept liability for error or omission.